

DMIX

25-100



12B



www.enginplast.com www.enginplast.com www.enginplast.com

EP
Enginplast



- Granulators
- Feeding systems
- Gravimetric dosers
- Volumetric dosers

Technical data - Control panel - Uses

Technical Data

MODEL		DMIX 25	DMIX 50	DMIX 75	DMIX 100
Maximum Flow	kg/h	200	400	600	800
N° max Dosers	N°	4	4	4	4
Dosers Motor Power	kW	0,18/0,25	0,18/0,25	0,18/0,25/0,37	0,18/0,25/0,55
Mixer motor Power	kW	0,37	0,75	0,75	0,75
Agitator Paddle type	-	Vertical	Vertical	Vertical	Vertical
Agitator Paddle speed	rpm	18	18	18	18
Dimension AxBxC	mm	446x398x630	547x477x823	627x477x982	577x477x1126
Mixer Capacity	dm ³	25	50	75	100

Control panel



APPLICATION : • Extrusion • Blowmoulding
• Injectionmoulding

MATERIALS : • Granule
• Grinded material

ADVANTAGES

- Blends removal beside the machine.
- Quick product changeover.
- Homogenous blend even with different types of material.
- Continuous feeding of extruder.

Dimensions



Uses



* NOTE : Technical data and images are indicative only and subject to possible changes. Engin Plast reserves the right to make changes for improvement without prior notice.



Address

Via per Zerbinate 29/A
44012 Bondeno (Fe) - Italy
P.iva e C.F. IT 01515370383 REA 174026

Contacts

Web : www.enginplast.com
Mail : sales@enginplast.com
Telephone: +39 0532 897178 - Fax: +39 0532 896362

